

Mould On Tires

Mould on Tires also called cured on tires. the rims connect with tires during the production. The wheel baseband is made according to the fitting specification of the vehicles' pivot bracket, and the thickness and the structure can be adjusted base on the tire loading.

After Treating to the base bands, curing reasonable rubber around the baseband surface to guarantee the loading of tires and other usage performance. --Smaller deformation , better stability and security.

--Running smoothly , slight shaking and twittering.

--Low rolling resistance, deducing energy consumption. Basebands can be recycled reducing cost and in accordance with the world trend of low-carbon economy.

--Easy assembling, no need to fit rims. Can be fixed to the vehicles and facilities directly , no worry for slipping

--Lower heat built up, good heat yield , over come the blow-out problems.

--Heavier loading, 10-15% increase of loading than the same size of tires



Character of usage



--Smaller deformation , better stability and security.

--Running smoothly , slight shaking and twittering.

--Low rolling resistance, deducing energy consumption. Basebands can be recycled reducing cost and in accordance with the world trend of low-carbon economy.

--Easy assembling, no need to fit rims. Can be fixed to the vehicles and facilities directly , no worry for slipping

--Lower heat built up, good heat yield , over come the blow-out problems.

--Heavier loading, 10-15% increase of loading than the same size of tires

Size and Pattern available



R708



R709

R711

序号No.	Size of Tire	With Hole (Yes/No)	Pattern No.	Outside Diamete ±5mm	Section Width ±5mm	Net Weight(Kg) ±1.5%kg	Max Load (kgs) 16Km/h
1	FB12.00-20	No	R701	1116	285	113	7645
2	FB 14.00-20	No	R706	1250	316	115	9496
3	FB10x16.5 (30x10-16)	Yes	R708	788	250	116	3700
4	FB12x16.5 (33x12-20)	Yes	R708	840	275	140	4500
5	FB16/70-20	Yes	R708	1060	400	329	8830
6	FB 16/70-20(经济型)	Yes	R708	940	330	216	6620
7	FB38.5x14-20(14x17.5,385/65D-19.5)	Yes	R708	966	350	246	7070
8	FB385/65-24 (385/65-22.5)	Yes	R708	1062	356	290	7390
9	FB445/65-24 (445/65-22.5)	Yes	R708	1152	428	394	10040
10	FB14.00-24	No	R701	1340	328	461	10700
11	FB17.5-25	Yes	R709	1368	458	650	13400
12	FB18.00-25	Yes	R711	1620	500	960	15795
13	FB20.5-25	No	R709	1455	500	950	17470
14	FB23.5-25	Yes	R709	1620	580	1040	23400
15	FB26.5-25	Yes	R709	1736	650	1395	29260
16	FB29.5-25	Yes	R709	1840	730	1780	34390

More about us

Certificate



Factory



Loading---Bulk loading or Pallet loading will follow customer requirement



WonRay on Tires expo

